

# **AMSOIL Synthetic Marine Engine Oil**

10W-30 & 10W-40

AMSOIL Synthetic Marine Engine Oil is a premium synthetic formulation designed to withstand the heat and stress of high-rpm operation and deliver excellent wear protection. It protects against rust and corrosion during periods of inactivity and long-term storage to keep your engine protected, even when it's not running. Synthetic Marine Engine Oil is perfect for hardcore anglers and boating enthusiasts who demand the best protection for their marine engines.

# **Fights Engine Wear**

AMSOIL Synthetic Marine Engine Oil's naturally strong base oils resist viscosity loss due to mechanical shear. The oil develops a tough lubricating film that protects engine parts, even in high-heat, high-rpm conditions that breakdown other oils. Synthetic Marine Engine Oil contains robust anti-wear additives that further reduce wear in metal-to-metal contact regions, guarding against compression loss for maximum power and extending the lives of marine engines.

#### **Excellent Anti-Rust Performance**

Good rust protection is not natural to motor oil; it comes only by design. AMSOIL Synthetic Marine Engine Oil is fortified with potent inhibitors that guard against damaging rust and corrosion. It protects engines during use and during inactivity or long-term storage.

### **NMMA Certified**

Synthetic Marine Engine Oil is certified by the National Marine Manufacturers Association (NMMA) for use in four-stroke outboard motors. This high-quality oil demonstrates outstanding performance and meets the requirements of the NMMA FC-W Catalyst Compatible specification, which is backward-compatible with the FC-W specification.

- 10W-40 FC-W (CAT)® Registration Number: FC-00850T
- 10W-30 FC-W (CAT)® Registration Number: FC-00833T



- Excellent high-stress, high-rpm endurance
- Increased rust and corrosion protection
- NMMA FC-W Catalyst Compatible

<sup>\*</sup>All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use. All products advertised here are developed by AMSOIL for use in the applications shown.

## TYPICAL TECHNICAL PROPERTIES

# AMSOIL Synthetic Marine Engine Oil

10W-30 (WCT)	10W-40 (WCF)
Kinematic Viscosity @ 100°C, cSt (ASTM D445)	14.1
Kinematic Viscosity @ 40°C, cSt (ASTM D445)	93.3
Viscosity Index (ASTM D2270)	155
Pour Point °C (°F) (ASTM D97)	-38 (-36)
Flash Point °C (°F) (ASTM D92)	240 (464)
High-Temperature/High-Shear Viscosity (ASTM D5481)	4.2
Four-Ball Wear Test	
(ASTM D4172 @ 40kgf, 150°C 1800 rpm, 1 hr), Scar, mm	0.40
NOACK Volatility, % weight loss (g/100g) (ASTM D5800)	7.5
Total Base Number	7.9

## **APPLICATIONS**

Use in gasoline-fueled four-stroke inboards, outboards, inboard/outboards and personal watercraft, including those made by Honda\*, Mercury\*, Yamaha\*, Johnson/Evinrude\*, Bombardier/BRP\*, Suzuki\*, Nissan\*, Tohatsu\*, OMC\*, Volvo-Penta\*, Mercruiser\*, Chevrolet\* and Ford\*.

NMMA FC-W Catalyst Compatible • API SM

#### **SERVICE LIFE**

- Four-stroke outboard motors and personal watercraft applications: Due to potential fuel dilution or water contamination, change oil at the engine or watercraft manufacturer-recommended interval.
- Inboard and I/O applications: Change oil at two times the engine manufacturer-recommended interval or one year, whichever comes first.

## **COMPATIBILITY**

AMSOIL Synthetic Marine Engine Oil is compatible with other synthetic and conventional motor oils. Adding other oils, however, will shorten the life expectancy of AMSOIL motor oils and reduce their performance benefits. AMSOIL does not support extended drain intervals where oils have been mixed.

Aftermarket oil additives are not recommended for use with AMSOIL Synthetic Marine Engine Oil.

# WARRANTY SECURE®

AMSOIL Synthetic Marine Engine Oil is Warranty Secure, keeping your factory warranty intact. AMSOIL Synthetic Marine Engine Oil is a high-performance replacement for vehicle manufacturer-branded



products and is also backed by the AMSOIL Limited Warranty. For details, visit www.amsoil.com/warrantysecure.

#### **HEALTH & SAFETY**

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available online at www.amsoil.com or upon request at (715) 392-7101. Keep Out of Reach of Children. Recycle used oil and bottle.

The First in Synthetics ®

AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.